



DC BLOWER

ADDA

Bearing type: ◎=Ball "B" ※=Sleeve "S" ○=1B1S "B(S)" ●=Hypro bearing "X"

PHOTO	Frame size (mm)	Model No.	Bearing Type B S B(S) X		Voltage (v)	Current (A)	Power (W)	Speed (rpm)	Maximum AirFlow		Maximum Pressure		Noise (dB/A)	Weight (g)	
			B	S					B(S)	X	(CMM)	(CFM)			(InAq)
	30x30x10	AB0305MX-GA0	◎	○	●	5	0.15	0.75	7500	0.028	0.98	0.176	4.41	28.0	12
		AB0305HX-GA0	◎	○	●	5	0.20	1.00	9000	0.034	1.20	0.263	6.59	33.0	
		AB0312MB-GA0	◎	○	●	12	0.09	0.96	7500	0.028	0.98	0.176	4.41	28.0	
		AB0312HB-GA0	◎	○	●	12	0.10	1.20	9000	0.034	1.20	0.263	6.59	33.0	
		AB0305MX-GA6	◎	○	●	5	0.15	0.75	7500	0.028	0.98	0.176	4.41	28.0	
		AB0305HX-GA6	◎	○	●	5	0.20	1.00	9000	0.034	1.20	0.263	6.59	33.0	
		AB0312MB-GA6	◎	○	●	12	0.09	0.96	7500	0.028	0.98	0.176	4.41	28.0	
		AB0312HB-GA6	◎	○	●	12	0.10	1.20	9000	0.034	1.20	0.263	6.59	33.0	
	35x35x07	AB3505LX-QB0		○	●	5	0.10	0.50	5500	0.003	0.09	0.126	3.20	19.0	13
		AB3505MX-QB0		○	●	5	0.14	0.70	6500	0.031	1.11	0.192	4.79	23.0	
		AB3505HX-QB0		○	●	5	0.23	1.15	7500	0.038	1.33	0.260	6.51	28.3	
		AB3512MX-QB0		○	●	12	0.12	0.14	6500	0.031	1.11	0.192	4.79	23.0	
	35x35x10	AB3505LB-GA0	◎	○		5	0.09	0.45	5000	0.026	0.91	0.042	1.05	23.0	16
		AB3505MX-GA0	◎	○	●	5	0.11	0.55	6000	0.035	1.22	0.153	3.84	27.5	
		AB3505HX-GA0	◎	○	●	5	0.17	0.85	7000	0.043	1.52	0.199	4.98	30.7	
		AB3512LX-GA0		○	●	12	0.11	0.13	5000	0.026	0.91	0.042	1.05	23.0	
		AB3512MB-GA0	◎	○	●	12	0.09	0.11	6000	0.035	1.22	0.153	3.84	27.5	
		AB3512HB-GA0	◎	○		12	0.10	0.12	7000	0.043	1.52	0.199	4.98	30.7	
	45x45x07	AB4505LB-QA0(S)		○		5	0.07	0.35	4700	0.042	1.50	0.202	5.13	23.3	23
		AB4505MB-QA0(S)		○		5	0.11	0.55	5500	0.048	1.70	0.289	7.33	27.9	
		AB4505HB-QA0(S)		○		5	0.14	0.70	6200	0.059	2.10	0.391	9.93	31.2	
		AB4505LX-QA0			●	5	0.07	0.35	4300	0.039	1.37	0.163	4.13	20.8	
		AB4505MX-QA0			●	5	0.11	0.55	5000	0.044	1.56	0.230	5.83	25.8	
		AB4505HX-QA0			●	5	0.14	0.70	5700	0.052	1.83	0.320	8.14	28.7	
		AB4512LB-QA0(S)		○		12	0.08	0.96	4700	0.042	1.50	0.202	5.13	23.3	
		AB4512MB-QA0(S)		○		12	0.09	1.08	5500	0.048	1.70	0.289	7.33	27.9	
		AB4512HB-QA0(S)		○		12	0.10	1.20	6200	0.059	2.10	0.391	9.93	31.2	
	45x45x10	AB4505MB-GD1(B)	◎	※	●	5	0.15	0.75	5000	0.065	2.31	0.348	8.69	31.1	25
		AB4505LB-GD1(B)	◎	※	●	5	0.13	0.30	4000	0.051	1.80	0.221	5.53	24.5	

DC Blower

Specifications subject to change without notice.



DC BLOWER



Bearing type: ⊙=Ball "B" ※=Sleeve "S" ○=1B1S "B(S)" ●=Hypro bearing "X"

PHOTO	Frame size (mm)	Model No.	Bearing Type B S B(S) X	Voltage (VDC)	Current (A)	Power (W)	Speed (rpm)	Maximum AirFlow		Maximum Pressure		Noise (dB/A)	Weight (g)
								(CMM)	(CFM)	(InAq)	(mmAq)		
	50x50x09	AB0505LB-RB1	⊙ ※ ●	5	0.12	0.60	4000	0.059	2.08	0.158	3.94	31.7	31.5
		AB0505MB-RB1	⊙ ※ ●	5	0.17	0.85	5000	0.085	3.00	0.291	7.28	30.5	
	50x50x20	AB5012HB-C01	⊙ ※ ●	12	0.21	2.52	6000	0.159	5.65	0.747	18.68	36.7	28
		AB5012MB-C01	⊙ ※ ●	12	0.12	1.44	5000	0.130	4.60	0.491	12.27	31.3	
		AB5012LB-C01	⊙ ※ ●	12	0.09	1.08	4000	0.104	3.70	0.240	6.00	24.5	
	70x70x12	AB7012HB-E01	⊙	12	0.18	2.16	3800	0.183	6.48	0.419	10.48	34.0	35
		AB7012LB-E01	⊙	12	0.10	1.20	2700	0.117	4.16	0.151	3.78	20.5	
	75x75x30	AD7512LB	⊙ ※ ●	12	0.11	1.32	2200	0.184	6.50	0.151	3.77	29.0	100
		AD7512MB	⊙ ※ ●	12	0.15	1.80	2600	0.220	7.78	0.234	5.84	34.9	
		AD7512HB	⊙ ※ ●	12	0.24	2.88	3000	0.258	9.11	0.330	8.24	38.5	
		AD7512UB	⊙ ※ ●	12	0.52	6.24	4200	0.369	13.05	0.723	18.07	44.7	
		AD7524LB	⊙ ※ ●	24	0.08	1.92	2200	0.184	6.50	0.151	3.77	29.0	
		AD7524MB	⊙ ※ ●	24	0.14	3.36	2600	0.220	7.78	0.234	5.84	34.9	
		AD7524HB	⊙ ※ ●	24	0.16	3.84	3000	0.258	9.11	0.330	8.24	38.5	
		AD7524UB	⊙ ※ ●	24	0.27	6.48	4200	0.369	13.05	0.723	18.07	44.7	
	94x94x33	AB0912HB-Z01	⊙	12	1.10	13.20	4000	0.614	33.10	0.909	29.21	54.2	140
		AB0912MB-Z01	⊙	12	0.90	10.80	3600	0.892	31.40	1.020	25.90	51.5	
		AB0912LB-Z01	⊙	12	0.57	6.84	3200	0.747	26.30	0.751	19.07	47.8	
		AB0912DB-Z01	⊙	12	0.41	4.92	2800	0.614	21.80	0.565	14.35	46.6	
	120x120x32	AB1212DB-Y01	⊙ ※ ●	12	0.30	3.60	1800	0.619	21.97	0.434	10.85	46.6	276
		AB1212LB-Y01	⊙ ※ ●	12	0.45	5.40	2100	0.718	25.48	0.659	16.47	48.0	
		AB1212MB-Y01	⊙ ※ ●	12	0.56	6.72	2300	0.791	28.09	0.829	20.72	49.0	
		AB1212HB-Y01	⊙ ※ ●	12	0.89	10.68	2600	0.881	31.28	0.916	22.90	55.0	
		AB1212UB-Y01	⊙ ※ ●	12	1.10	13.20	2800	0.940	33.40	1.148	28.70	53.3	
		AB1212XB-Y01	⊙	12	1.40	16.80	3100	1.070	38.00	1.412	35.30	57.0	
		AB1224DB-Y01	⊙ ※ ●	24	0.20	4.80	1800	0.619	21.97	0.434	10.85	46.6	
		AB1224LB-Y01	⊙ ※ ●	24	0.30	7.20	2100	0.718	25.48	0.659	16.47	48.0	
		AB1224MB-Y01	⊙ ※ ●	24	0.39	9.36	2300	0.791	28.09	0.829	20.72	49.0	
		AB1224HB-Y01	⊙ ※ ●	24	0.49	11.76	2600	0.881	31.28	0.916	22.90	55.0	
		AB1224UB-Y01	⊙ ※ ●	24	0.55	13.20	2800	0.940	33.40	1.148	28.70	53.3	
		AB1224XB-Y01	⊙	24	0.71	17.04	3100	1.070	38.00	1.412	35.30	57.0	
		AB1248DB-Y01	⊙ ※ ●	48	0.12	5.76	1800	0.619	21.97	0.434	10.85	46.6	
		AB1248LB-Y01	⊙ ※ ●	48	0.17	8.16	2100	0.718	25.48	0.659	16.47	48.0	
		AB1248MB-Y01	⊙ ※ ●	48	0.20	9.60	2300	0.791	28.09	0.829	20.72	49.0	
		AB1248HB-Y01	⊙ ※ ●	48	0.24	11.52	2600	0.881	31.28	0.916	22.90	55.0	
AB1248UB-Y01	⊙ ※ ●	48	0.34	16.32	2800	0.940	33.40	1.148	28.70	53.3			

Specifications subject to change without notice.

