







**BRACKET FAN**




Bearing type: ⊙=Ball "B" ※=Sleeve "S" ○=1B1S "B(S)" ●=Hypro bearing "X"


| PHOTO  | Frame size (mm) | Model No.               | Bearing Type B S B(S) X | Voltage (VDC) | Current (A) | Power (W)   | Speed (rpm)           | Maximum AirFlow (CMM) | Maximum AirFlow (CFM)   | Maximum Pressure (InAq) | Maximum Pressure (mmAq) | Noise (dB/A) | Weight (g) |
|--|-----------------|-------------------------|-------------------------|---------------|-------------|-------------|-----------------------|-----------------------|-------------------------|-------------------------|-------------------------|--------------|------------|
| (mm) Frame size  | Model No.       | B S B(S) X Bearing Type | (VDC) Voltage           | (A) Current   | (W) Power   | (rpm) Speed | (CMM) Maximum AirFlow | (CFM) Maximum AirFlow | (InAq) Maximum Pressure | (mmAq) Maximum Pressure | (dB/A) Noise            | (g) Weight   |            |
|  | 60X60X11        | AD0605HB-TB3 (CWY73L3)  | ⊙                       | 5             | 0.25        | 1.25        | 4100                  | 0.085                 | 3.00                    | 0.20                    | 5.08                    | 30.0         | 12.5       |
|  | Ø40X13          | AD0405HB-HB3 (CW4Y85)   | ●                       | 5             | 0.25        | 1.25        | 4600                  | 0.085                 | 3.00                    | 0.32                    | 8.13                    | 33.0         | 9          |
|  | Ø58X11          | AD0405HX-KC3 (Y14X)     | ●                       | 5             | 0.4         | 2.0         | 3100                  | 0.195                 | 6.90                    | 0.37                    | 9.40                    | 44.0         | 9          |

 Specifications subject to change without notice.

**VGA COOLER**

Bearing type: ⊙=Ball "B" ※=Sleeve "S" ○=1B1S "B(S)" ●=Hypro bearing "X"

| PHOTO   | Frame size (mm) | Model No.               | Bearing Type B S B(S) X | Voltage (VDC) | Current (A) | Power (W)   | Speed (rpm)           | Maximum AirFlow (CMM) | Maximum AirFlow (CFM)   | Maximum Pressure (InAq) | Maximum Pressure (mmAq) | Noise (dB/A) | Weight (g) |
|---|-----------------|-------------------------|-------------------------|---------------|-------------|-------------|-----------------------|-----------------------|-------------------------|-------------------------|-------------------------|--------------|------------|
| (mm) Frame size   | Model No.       | B S B(S) X Bearing Type | (VDC) Voltage           | (A) Current   | (W) Power   | (rpm) Speed | (CMM) Maximum AirFlow | (CFM) Maximum AirFlow | (InAq) Maximum Pressure | (mmAq) Maximum Pressure | (dB/A) Noise            | (g) Weight   |            |
|  | 75X75X10        | AD0512UB-TB1 (CWC96)    | ●                       | 12            | 0.22        | 2.64        | 6000                  | 0.158                 | 5.60                    | 0.45                    | 11.43                   | 42.3         | 60         |
|   | 15.5X9          | AD512HB-E03 (R520SS)    | ⊙                       | 12            | 0.20        | 2.30        | 5000                  | 0.093                 | 3.30                    | 0.38                    | 9.65                    | 39.0         | 285        |
|   | 214X90X35       | AD0912LB-A73GL(B) TM40B | ●                       | 12            | 0.17        | 2.04        | 2300                  | 0.486                 | 17.17                   | 0.122                   | 3.10                    | 37.1         | 250        |

 Specifications subject to change without notice.