

MILITARY PART NO.	WIRE AWC/STRAND	RESISTANCE AT 20° C. OHMS 1000' MAX.	NOMINAL DIAMETER		MAXIMUM WEIGHT	
			INCHES	MILLIMETERS	POUNDS/1000'	KILOGRAMS/ KILOMETERS
22759/45-28-*	28 7/36	67.9	.027	.686	.91	1.35
22759/45-26-*	26 19/38	42.2	.032	.813	1.4	2.08
22759/45-24-*	24 19/36	25.9	.037	.940	2.0	2.98
22759/45-22-*	22 19/34	16.0	.043	1.092	2.8	4.17
22759/45-20-*	20 19/32	9.77	.050	1.270	4.3	6.40
22759/45-18-*	18 19/30	6.10	.060	1.524	6.5	9.67
22759/45-16-*	16 19/29	4.76	.068	1.727	8.3	12.35
22759/45-14-*	14 19/27	3.00	.085	2.159	13.0	19.35
22759/45-12-*	12 37/28	1.98	.103	2.616	19.7	29.32

MILITARY PART NO.	WIRE AWG/STRAND	RESISTANCE AT 20° C. OHMS 1000' MAX.	NOMINAL DIAMETER		MAXIMUM WEIGHT	
			INCHES	MILLIMETERS	POUNDS/1000'	KILOGRAMS/ KILOMETERS
22759/46-28-*	28 7/36	79.0	.027	.686	.91	1.35
22759/46-26-*	26 19/38	49.4	.032	.813	1.4	2.08
22759/46-24-*	24 19/36	30.1	.037	.940	2.0	2.98
22759/46-22-*	22 19/34	18.6	.043	1.092	2.9	4.32
22759/46-20-*	20 19/32	11.4	.050	1.270	4.4	6.55