



ARINC 600 Rack & Panel Filter Connectors TBKAD

The Challenge

Today's commercial aerospace avionics manufacturers require higher density Rack and Panel connectors, and are placing more and more emphasis on the need to protect critical electronic systems from EMI, voltage transients and voltage surges at the connector interface.

The Solution

An ARINC 600 Filter provides the highest density pin outs, and the highly robust TBKAD Filter connector version provides the system-level EMI protection in the most effective way, as the box interface.



The CANNON Difference

- Highly engineered, off-the-shelf and customized solutions
- Designed for performance & reliability in the harshest environments
- A committed partner with more than a century of interconnect solutions excellence

Key Product Features

- Up to 800 size 22 contacts in one connector
- Low insertion force contacts
- Crimp, co-ax, power, printed circuit, and wire wrap post style contacts
- Meets the vibration and sealing requirements of ARINC 600
- Available in a wide range of planar array and Chip-on-Flex capacitor values tailored for each circuit
- Design options include MOV and diodes versions for TVS and surge protection

Markets & Applications



COMMERCIAL AEROSPACE

NAVIGATION SYSTEMS, RADAR SYSTEMS,
AVIONICS, FLIGHT CONTROL SYSTEMS,
FLIGHT MANAGEMENT, TCAS



MILITARY & DEFENSE

MISSION COMPUTERS, NAVIGATION
AND FLIGHT CONTROLS

TBKA

D

2

100

M

4

80

81

*

**Filter Connector Series

Class

Shell Size

Connector Layout Description

Capacitance Indicator

Shell Style

Connector Mounting Modifier

Polarizing Position

Special Modifier

Filter Connector Series
TBKA (Per ARINC 600)
* * Consult factory for availability.

Class
D - Non-environmental (rear release, crimp contacts)

Connector Layout Description
Three digit number contained within the shell layout indicates total number of contacts available


Connector Layout	Shell Size	Shell Cavity Identification					
		A	B	C	D	E	F
-060	1	-	60	-			
-A060	1	60	-	-			
-120	1	60	60	-			
-100	2	-	-	100			
-300	2	150	150	-			
-400	2	150	150	100			
-600	3	150	150	-	150	150	-
-800	3	150	150	100	150	150	150

Shell Size
1 - Max. contact capacity - 125
2 - Max. contact capacity - 400
3 - Max. contact capacity - 800

Why ITT

ITT is a focused multi-industrial company that designs and manufactures highly engineered critical components and customized technology solutions. ITT's Cannon brand is a leading global manufacturer of connector products serving international customers in aerospace, defense, medical, industrial and transportation end markets. ITT's Connector business, which also includes the Veam and BIW Connector Systems brand, manufactures and supplies a variety of connectors and interconnects that make it possible to transfer data, signal and power in an increasingly connected world.

Connect with your ITT Cannon representative today or visit ittcannon.com

Follow us 

CHINA - Shenzhen City +86.755.2726.7888	GERMANY - Weinstadt +49.7151.699.0	ITALY - Lainate +39.02938721	KOREA +82.2.702.7111	SHANGHAI + 86.21.2231.2222	UK - Basingstoke +44.1256.347400
FRANCE +33.1.60.04.93.93	HONG KONG +852.2732.2720	JAPAN - Kanagawa +81.462.57.2010	MEXICO - Nogales +52.631.3110050	SINGAPORE +65 66974205	USA - Irvine, CA +1.800.854.3028

Connector Size	# of Clinch Nuts
	Receptacle
1	4
2	6
3	10

08 - Size 2 and 3 receptacle only-with #4-40 ESMA (#22 NCFMA2-40) clinch nuts (all mounting holes)
09 - Size 2 and 3 receptacle only-with #6-32 ESMA (#12 NCFMA2062) clinch nuts (all mounting holes)
23 - With floating eyelets (.048 min. radial float) 4 corner holes per connector

Consult factory if other modifications are required.

Polarizing Position
01 thru 99 (per ARINC 600)
Blank-Polarizing posts or keys not installed but supplied with connector

Special Modifier
Consult factory

