

Product: BTL12-08T1-02TX-L

BEETLE Single Pair Ethernet Lite Managed Switch

Product Description Lite Managed SPE Switch with 8x M8 SPE-ports and 10Base-T1L and 2x RJ45 Fast Ethernet.

Technical Specifications

Product description

Name:	BTL-1-L-5-1-6-W2-08T1-2-02TX-S-Z9-HH-HH
Part Number:	935800001
Port type and quantity:	2 x 10/100BASE-TX 8 x 10BASE-T1L
Displays	
LEDs:	Power, Port State, Device Status, PoDL
More Interfaces	
Power supply/signaling contact:	1 x plug-in terminal block, 6-pin
Network size - length o	of cable
Twisted pair (TP):	0-100 m
Single Pair (SP):	0-1000 m
Power requirements	
Operating Voltage:	24 VDC
Software	
Switching:	VLAN (802.1Q), QoS/Port Prioritization (802.1D/p), TOS/DSCP Prioritization, CoS Queue Management, Queue-Shaping/Max. Queue Bandwidth, Unknown Multicast Filtering, Egress Interface Shaping, Ingress Storm Protection
Management:	LLDP (802.1AB), Password change on first login, HTTP, Responsive GUI
Diagnostics:	LEDs, Device Status Indication, Syslog, Link Speed and Duplex Monitoring, SPE cable diagnosis
Configuration:	Web-based Management, OPC-UA
Security:	Local User Management, MAC based ACL
Miscellaneous:	PoDL (IEEE 802.3cg)
Ambient conditions	

Operating temperature:	-10-+60 °C
Storage/transport temperature:	-40°C to + 70 °C
Relative humidity (non-condensing):	1-95 %

Mechanical construction

Dimensions (WxHxD):	61 x 163.6 x 114.7 mm
Weight:	1016 g
Mounting:	DIN Rail
Protection class:	IP40

Scope of delivery and accessories

Accessories to Order Separately:	DataTuff SPE cables, SPE connectors, RPS power supply
Scope of delivery:	Device, Terminal Block, Start-up Instructions, Saftey Instructions
History	
Update and Revision:	Revision Number: 0.21 Revision Date: 03-01-2024
Update and Revision: Variants	Revision Number: 0.21 Revision Date: 03-01-2024
	Revision Number: 0.21 Revision Date: 03-01-2024

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.