


MHD / MDD / MDP Connectors Series


PCB High Density Connectors



Hypertac® Hyperboloid Technology

Smiths Interconnect offers an extensive range of superior contact technologies suitable for standard and custom solutions. Hypertac® (HYPERboloid conTACT) is the original superior performing hyperboloid contact technology designed for use in all applications and in harsh and demanding environments where high reliability and safety are critical. The inherent electrical and mechanical characteristics of the Hypertac hyperboloid contact ensures unrivalled performance in terms of reliability, number of mating cycles, low contact force and minimal contact resistance.

The shape of the contact sleeve is formed by hyperbolically arranged contact wires, which align themselves elastically as contact lines around the pin, providing a number of linear contact paths.



Features

Low insertion/extraction forces

The angle of the socket wires allows tight control of the pin insertion and extraction forces. The spring wires are smoothly deflected to make line contact with the pin.

Long contact life

The smooth and light wiping action minimizes wear on the contact surfaces. Contacts perform up to 100,000 insertion/extraction cycles with minimal degradation in performance.

Lower contact resistance

The design provides a far greater contact area and the wiping action of the wires insures a clean and polished contact surface. Our contact technology has about half the resistance of conventional contact designs.

Higher current ratings

The design parameters of the contact (e.g., the number, diameter and angle of the wires) may be modified for any requirement. The number of wires can be increased so the contact area is distributed over a larger surface. Thus, the high current carried by each wire because of its intimate line contact, can be multiplied many times.

Immunity to shock & vibration

The low mass and resultant low inertia of the wires enable them to follow the most abrupt or extreme excursions of the pin without loss of contact. The contact area extends 360° around the pin and is uniform over its entire length. The 3 dimensional symmetry of the Hypertac contact design guarantees electrical continuity in all circumstances.

Benefits

High density interconnect systems

Significant reductions in size and weight of sub-system designs. No additional hardware is required to overcome mating and unmating forces.

Low cost of ownership

The Hypertac contact technology will surpass most product requirements, thus eliminating the burden and cost of having to replace the connector or the entire subsystem.

Low power consumption

The lower contact resistance of our technology results in a lower voltage drop across the connector reducing the power consumption and heat generation within the system.

Maximum contact performance

The lower contact resistance of the Hypertac contact reduces heat build-up; therefore Hypertac contacts are able to handle far greater current in smaller contact assemblies without the detrimental effects of high temperature.

Reliability under harsh environments

Harsh environmental conditions require connectors that will sustain their electrical integrity even under the most demanding conditions such as shock and vibration. The Hypertac contact provides unmatched stability in demanding environments when failure is not an option.

Contents

MHD Series

Technical characteristics	2
How to order.....	3
Modules configuration.....	4
Standard plugging stages.....	5
Termination styles.....	6
Connector dimensions	7
Guiding devices	13
Contact board preparation details	14
Power and high frequency contacts	18

MDD Series

Technical characteristics	19
How to order.....	20
Modules configuration.....	21
Standard plugging stages.....	22
Termination styles.....	23
Connector dimensions	24
Guiding devices	25
Contact board preparation details	26

MDP Series

Technical characteristics	27
How to order.....	28
Connector dimensions	29
Guide and termination styles	30
Contact board preparation details	31

Technical Characteristics

Materials & Platings

Insulator	Diallyl Phthalate UL94V0
Frame	Aluminium Alloy
Contact	Copper Alloy
Guide	Brass + Ni plating or Stainless Steel
Contact plating	Ni + Au

Environmental

Temperature range	- 55° C to +125° C
Safety of contact from extraction	Statical 2 mm / 0.079" Dynamical 1.80 mm / 0.071"
Mating cycles	5000
Withdrawal forces	≤ 0.5 N
Special contacts	According to NFC 93569

Electrical

Contact resistance	Signal ≤ 12 mΩ Power ≤ 2 mΩ
Current rating	Signal 3 A Power 15 A
Insulation	>10 ⁴ MΩ
Voltage rating	200 V
Proof voltage	800 V
Contact diameter	Signal 0.50 mm Power 2.00 mm
Impedance	Coaxial 50 Ω

How To Order



Code ESA

3401-065 01B



Code HYPERTAC

MHD



1

2

3

4

5

1 Series	
2 Arrangement	<p> Ⓢ 052 Ⓢ 152 Ⓢ 252 Ⓢ 352 5HA 1HB 6XA Ⓢ 100 Ⓢ 200 Ⓢ 300 Ⓢ 400 2XA 7XB 3HB </p>
3 Part - Polarity Plating	<p> 13 Ⓢ 55 Male Plug Standard plating 22 Ⓢ 44 Female Receptacle Standard plating 17 Ⓢ 57 Male Plug Pretinned 26 Ⓢ 46 Female Receptacle Pretinned </p>
4 Termination Styles	<p> Ⓢ 10 90° termination, PCB thickness 1.60 Ⓢ 11¹⁾ 90° termination, PCB thickness 2.40 Ⓢ 12²⁾ 90° termination, PCB thickness 3.20 Ⓢ 30 Straight termination, PCB thickness 2.40 Ⓢ 31 Straight termination, PCB thickness 3.20 41 SMT³⁾ - PCB thickness 1.60 42 SMT³⁾ - PCB thickness 3.20 Ⓢ 43 SMT³⁾ - PCB thickness 2.40 44 SMT³⁾ - Uncentered PCB thickness 3.80 Ⓢ 45 SMT³⁾ - Uncentered PCB thickness 1.60 Ⓢ 47 SMT³⁾ - Uncentered PCB thickness 2.40 Ⓢ 91 Female / male saver⁴⁾ </p>
5 Guide Styles	<p> Ⓢ 110 Male polarised, transverse mount, standard plug Ⓢ 111 Male polarised, vertical mount Ⓢ 121 Female polarised, vertical mount 122 Female polarised, vertical mount Ⓢ 124 Female polarised, transverse mount 125 Male unpolarised, transverse mount 126 Female unpolarised, vertical mount 130 Female polarised, vertical mount 131 Female polarised, vertical mount 133 Female all polarised, transverse mount Ⓢ 134 Female polarised, transverse mount 190 Female power or mass contact, vertical mount 191 Male power or mass contact, transverse mount Ⓢ 201 ¼ turn, free connector </p>

1) Available for receptacle connector

2) Available for plug connector

3) Surface Mount Termination









4) Consult us - PCB thickness is in mm

Modules Configuration

Single Arrangements

Receptacle Mating Side Views

Mixed Arrangements



26 ways module




50 ways module



4 ways module
(special contacts)



Space which can receive:
2x50 ways module
or
2x26 ways module
1x4 ways module
or
2x4 ways module




Space which can receive:
2x26 ways module
or
1x4 ways module


Standard Plugging Stages

Misalignment

Longitudinal




Lateral




Gap

Lateral




Tilting





Longitudinal



Lateral



Mounting Examples



Displacement

Max displacement allowed while plugging in the receptacle: 0.15 mm in all plugged in connector ways.


Termination Styles

Receptacle

Through board solder - 90°

Ref: 10
PCB: 1.44 - 1.76
A = 3.25^{+0.15}_{-0.45}
B = 6 max

Ref: 11
PCB: 1.98 - 2.42
A = 3.85^{+0.15}_{-0.45}
B = 6.60 max




* Unbuild-up of tolerances

Through board solder - Straight

Ref: 30
PCB: 2.16 - 2.64
A = 3.50 min
A = 4.00 max

Ref: 31
PCB: 2.88 - 5.50
A = 6.10 min
A = 6.60 max

Ref: 96
PCB: 3.42 - 4.18
A = 4.70 min
A = 5.10 max




Plug

Through board solder - 90°

Ref: 10
PCB: 1.44 - 1.76
A = 5.95 max

Ref: 12
PCB: 2.88 - 3.52
A = 7.60 max




* Unbuild-up of tolerances

Through board solder - Straight

Ref: 30
PCB: 2.16 - 2.64
A = 3.50 min
A = 4.00 max

Ref: 31
PCB: 2.88 - 3.52
A = 4.60 min
A = 5.10 max




Surface mount (centered PCB)


Ref: 41
PCB: 1.44 - 1.76
A = 5.20 max

Ref: 42
PCB: 2.88 - 3.52
A = 4.40 max

Ref: 43
PCB: 2.16 - 2.64
A = 4.80 max



Section of termination
Mandatory only for
termination 43, 45 & 47
(ESCC 3401-065)




Surface mount (uncentered PCB)

Ref: 44
PCB: 3.60 - 4.00
A = 4.40 max


Ref: 45
PCB: 1.44 - 2.40
A = 7 max

Ref: 47
PCB: 2.16 - 2.70
A = 7 max




Connector Dimensions

Plug




52 contacts





View mating side


Receptacle





100 contacts




View mating side





5HA




View mating side



1HB




View mating side




* Theoretical dimensions

The termination side contact configurations are specified on board preparation details.

152 Contacts Plug




Receptacle




View mating side

6XA Plug



Receptacle




View mating side


* Theoretical dimensions

The termination side contact configurations are specified on board preparation details.


200 Contacts Plug




Receptacle



2XA Plug




Receptacle




* Theoretical dimensions

The termination side contact configurations are specified on board preparation details.


252 Contacts Plug




Receptacle



7XB Plug




Receptacle




* Theoretical dimensions

The termination side contact configurations are specified on board preparation details.

300 Contacts Plug




Receptacle




View mating side

3HB Plug



Receptacle



View mating side


* Theoretical dimensions

The termination side contact configurations are specified on board preparation details.

352 Contacts

Plug


Receptacle



400 Contacts

Plug

Receptacle



* Theoretical dimensions


The termination side contact configurations are specified on board preparation details.

Guiding Devices

Receptacle


MHD 00- __ 121

Polarised female guide vertical mounting (Length: 5.50)




MHD 00- __ Z122

Polarised female guide vertical mounting (Length: 7)




MHD 00- __ Z124 / Z134

Polarised female guide transverse mounting P/N 124: A=6; 134: A=6.60




MHD 00- __ Z126

Unpolarised female guide vertical mounting




MHD 00- __ Z130

All polarity female guide vertical mounting (Length: 5.50)




MHD 00- __ Z131

All polarity female guide vertical mounting (Length: 7)




MHD 00- __ Z133

All polarity female guide transverse mounting



MHD 00- __ Z190


Ground female guide vertical mounting



Plug

MHD 00- __ 110


Polarised male guide transverse mounting



Mass per set: 0.55 gr.

MHD 00- __ Z111


Polarised male guide vertical mounting



Mass per set: 1.35 gr.

MHD 00- __ Z125


Unpolarised male guide transverse mounting



Mass per st: 0.55 gr.

MHD 00- __ Z191

Ground male contact transverse mounting




* Theoretical dimensions

Contact Board Preparation Details

52 Contact Board Preparation Details ⁽¹⁾ Receptacle


Straight Termination

Guides: 121, 122, 126, 130, 131, 190



90° Termination


Guides: 124, 133, 134



Plug


Straight Termination

Guides: 111




90° Termination

Guides: 110, 125, 191



Surface mount termination

Guides: 110, 125, 191



(1) Important note: See important note on 1HB preparation board details (page 17).


* Theoretical dimensions

5HA Contact Board Preparation Details ⁽¹⁾

Receptacle


Straight Termination

Guides: 121, 122, 126, 130, 131, 190



90° Termination


Guides: 124, 133, 134



Plug


90° Termination

Guides: 110, 125, 191



Surface mount termination

Guides: 110, 125, 191



(1) **Important note:** See important note on 1HB preparation board details (page 17).


* Theoretical dimensions

100 Contact Board Preparation Details ⁽¹⁾

Receptacle


Straight termination

Guides: 121, 122, 126, 130, 131, 190



90° Termination


Guides: 124, 133, 134



Plug


Straight termination

Guides: 111




90° Termination

Guides: 110, 125, 191



Surface mount termination

Guides: 110, 125, 191



(1) Important note: See important note on 1HB preparation board details (page 17).

* Theoretical dimensions

1HB Contact Board Preparation Details ⁽¹⁾



Receptacle

Straight termination

Guides: 121, 122, 126, 130, 131, 190

90° Termination

Guides: 124, 133, 134





Plug

90° Termination

Guides: 110, 125, 191

Surface mount termination

Guides: 110, 125, 191




(1) Important note: Drilling layouts shown concern the following full configurations: 052, 5HA, 100, 1HB, 200. Other arrangements, shown on "MODULES CONFIGURATION" page, require a specific drilling layout to ensure the correct mounting of the chosen connector, that you must obtain from our technical department. However, the drilling layouts shown above should help you to achieve the desired configuration. For that, you may have to mix those drilling layouts to obtain the right configuration.

* Theoretical dimensions

Power & High Frequency Contacts *(NFC 93569)*

Example of Contact Overview *(020 084 2- 10 RG1)*



Power Contacts

Male	P/N
90° termination	020 085 1- 10R OG
Straight termination	020 087 1- 30R OG
Solder bucket termination	020 091 1- 40R OG

Female	P/N
90° termination	020 084 2- 10R G1
Straight termination	020 056 2- 30R G1
Solder bucket termination	020 060 2- 40R G1

High Frequency Contacts

	Male P/N	Female P/N
Vertical mounting, suitable for flexible cable \varnothing 1.9 max. Ref. KX 21 A (Rg 178 B/U or RG 196).	KMX 3-M 081	KMX 3-F 081
Transverse mounting, suitable for flexible cable \varnothing 1.9 max. Ref. KX 21 A (Rg 178 B/U or RG 196). Usable with mother board, thickness 3.2 mm max.	KMX 3-M 092	KMX 3-F 092
Vertical mounting, suitable for flexible cable \varnothing 2.5 max. Ref. KX 22 A (RG 316).	KMX 3-M 101	KMX 3-F 101
Transverse mounting, suitable for flexible cable \varnothing 2.5 max. Ref. KX 22 A (RG 316). Usable with mother board, thickness 3.2 mm max.	KMX 3-M 112	KMX 3-F 112
Vertical mounting, suitable to semi-rigid cable \varnothing 2.2 max. Ref. Ks 1 A (RG 405 - UT 85).	KMX 3-M 131	KMX 3-F 131
Transverse mounting, suitable to semi-rigid cable \varnothing 2.2 max. Ref. Ks 1 A (RG 405 - UT 85). Usable with mother board, thickness 3.2 mm max.	KMX 3-M 142	KMX 3-F 142
Straight termination tail for direct mounting on to PCB	KMX 3-M 041	KMX 3-F 041
90° termination tail for direct mounting on to PCB	KMX 3-M 032	KMX 3-F 032
SMT termination	KMX 3-M 172	KMX 3-F 172

Extraction Tools

P/N: SD- 030 00 CX 003

Technical Characteristics

Materials & Platings

Insulator	Diallyl Phtalate UL94V0
Frame	Aluminium Alloy
Contact	Copper Alloy
Guide	Brass + Ni plating or Stainless Steel
Contact plating	Ni + Au

Environmental

Temperature range	- 55° C to +125° C
Safety of contact from extraction	Statical 2 mm / 0.079" Dynamical 1.80 mm / 0.071"
Mating cycles	5000
Withdrawal forces	≤ 0.5 N
Special contacts	According to NFC 93569

Electrical

Contact resistance	Signal ≤ 12 mΩ
Current rating	Signal 3 A
Insulation	>10 ⁴ MΩ
Voltage rating	200 V
Proof voltage	800 V
Contact diameter	Signal 0.50 mm

How To Order



MDD

1



2



3



4





5

1 Series															
2 Arrangement	1 0 0 2 0 0														
3 Part - Polarity Plating	<table border="0"> <tr> <td>1 5 Male plug - MIL plating</td> <td>2 4 Female receptacle - MIL plating</td> </tr> <tr> <td>1 9 Male plug - MIL tinned plating</td> <td>2 8 Female receptacle - MIL tinned plating</td> </tr> </table>	1 5 Male plug - MIL plating	2 4 Female receptacle - MIL plating	1 9 Male plug - MIL tinned plating	2 8 Female receptacle - MIL tinned plating										
1 5 Male plug - MIL plating	2 4 Female receptacle - MIL plating														
1 9 Male plug - MIL tinned plating	2 8 Female receptacle - MIL tinned plating														
4 Termination Styles	<table border="0"> <tr> <td>1 0 90° termination, PCB thickness 1.60</td> <td>1 1 90° termination, PCB thickness 2.40</td> </tr> <tr> <td>3 0 Straight termination, PCB thickness 2.40</td> <td>3 1 Straight termination, PCB thickness 3.20</td> </tr> <tr> <td>4 4 SMT* - Uncentered PCB thickness 3.80</td> <td>9 6 Straight termination, PCB thickness 4.50</td> </tr> </table>	1 0 90° termination, PCB thickness 1.60	1 1 90° termination, PCB thickness 2.40	3 0 Straight termination, PCB thickness 2.40	3 1 Straight termination, PCB thickness 3.20	4 4 SMT* - Uncentered PCB thickness 3.80	9 6 Straight termination, PCB thickness 4.50								
1 0 90° termination, PCB thickness 1.60	1 1 90° termination, PCB thickness 2.40														
3 0 Straight termination, PCB thickness 2.40	3 1 Straight termination, PCB thickness 3.20														
4 4 SMT* - Uncentered PCB thickness 3.80	9 6 Straight termination, PCB thickness 4.50														
5 Guide Styles	<table border="0"> <tr> <td>1 1 0 Male polarised, transverse mount, standard plug</td> <td>1 1 1 Male polarised, vertical mount</td> </tr> <tr> <td>1 2 1 Female polarised, vertical mount</td> <td>1 2 2 Female polarised, vertical mount</td> </tr> <tr> <td>1 2 4 Female polarised, transverse mount</td> <td>1 2 5 Male unpolarised, transverse mount</td> </tr> <tr> <td>1 2 6 Female unpolarised, vertical mount</td> <td>1 3 0 Female all polarised, vertical mount</td> </tr> <tr> <td>1 3 1 Female all polarised, vertical mount</td> <td>1 3 3 Female all polarised, transverse mount</td> </tr> <tr> <td>1 3 4 Female polarised, transverse mount</td> <td>1 9 0 Female power or mass contact, vertical mount</td> </tr> <tr> <td>1 9 1 Male power or mass contact, transverse mount</td> <td>2 0 1 ¼ turn, free connector</td> </tr> </table>	1 1 0 Male polarised, transverse mount, standard plug	1 1 1 Male polarised, vertical mount	1 2 1 Female polarised, vertical mount	1 2 2 Female polarised, vertical mount	1 2 4 Female polarised, transverse mount	1 2 5 Male unpolarised, transverse mount	1 2 6 Female unpolarised, vertical mount	1 3 0 Female all polarised, vertical mount	1 3 1 Female all polarised, vertical mount	1 3 3 Female all polarised, transverse mount	1 3 4 Female polarised, transverse mount	1 9 0 Female power or mass contact, vertical mount	1 9 1 Male power or mass contact, transverse mount	2 0 1 ¼ turn, free connector
1 1 0 Male polarised, transverse mount, standard plug	1 1 1 Male polarised, vertical mount														
1 2 1 Female polarised, vertical mount	1 2 2 Female polarised, vertical mount														
1 2 4 Female polarised, transverse mount	1 2 5 Male unpolarised, transverse mount														
1 2 6 Female unpolarised, vertical mount	1 3 0 Female all polarised, vertical mount														
1 3 1 Female all polarised, vertical mount	1 3 3 Female all polarised, transverse mount														
1 3 4 Female polarised, transverse mount	1 9 0 Female power or mass contact, vertical mount														
1 9 1 Male power or mass contact, transverse mount	2 0 1 ¼ turn, free connector														

* Surface Mount Termination
PCB thickness is in mm

Modules Configuration

Receptacle - Mating Side Views Single arrangements




50 ways module




Standard Plugging Stages

Misalignment

Longitudinal




Lateral




Gap

Lateral




Tilting


Longitudinal



Lateral



Mounting Examples



Displacement

Max displacement allowed while plugging in the receptacle: 0.15 mm in all plugged in connector ways.


Termination Styles

Receptacle

Through board solder - 90°

Ref: 10
PCB: 1.44 - 1.76
 $A = 3.25^{+0.15}_{-0.45}$
 $B = 6 \text{ max}$

Ref: 11
PCB: 1.98 - 2.42
 $A = 3.85^{+0.15}_{-0.45}$
 $B = 6.60 \text{ max}$




* Unbuild-up of tolerances

Through board solder - Straight

Ref: 30
PCB: 2.16 - 2.64
 $A = 3.50 \text{ min}$
 4.00 max

Ref: 31
PCB: 2.88 - 5.50
 $A = 6.10 \text{ min}$
 6.60 max




Ref: 96
PCB: 3.42 - 4.18
 $A = 4.70 \text{ min}$
 5.10 max

Plug

Through board solder - 90°

Ref: 10
PCB: 1.44 - 1.76
 $A = 5.95 \text{ max}$




* Unbuild-up of tolerances

Through board solder - Straight


Ref: 30
PCB: 2.16 - 2.64
 $A = 3.50 \text{ min}$
 4.00 max

Ref: 31
PCB: 2.88 - 3.52
 $A = 4.60 \text{ min}$
 5.10 max




Surface Mount (uncentered PCB)

Ref: 44
PCB: 3.60 - 4.00
 $A = 4.40 \text{ max}$




Connector Dimensions


100 Contacts Plug




Receptacle



200 Contacts Plug



Receptacle




* Theoretical dimensions

Guiding Devices

Receptacle


MHD 00- __ 121

Polarised female guide vertical mounting (Length: 5.50)




MHD 00- __ Z122

Polarised female guide vertical mounting (Length: 7)




MHD 00- __ Z124 / Z134

Polarised female guide transverse mounting P/N 124: A=6; 134: A=6.60




MHD 00- __ Z126

Unpolarised female guide vertical mounting




MHD 00- __ Z130

All polarity female guide vertical mounting (Length: 5.50)




MHD 00- __ Z131

All polarity female guide vertical mounting (Length: 7)




MHD 00- __ Z133

All polarity female guide transverse mounting



MHD 00- __ Z190


Ground female guide vertical mounting



Plug


MHD 00- __ 110

Polarised male guide transverse mounting




MHD 00- __ Z111

Polarised male guide vertical mounting




MHD 00- __ Z125

Unpolarised male guide transverse mounting



MHD 00- __ Z191

Ground male contact transverse mounting



* Theoretical dimensions


Contact Board Preparation Details

100 Contact Board Preparation Details ⁽¹⁾

Receptacle


Straight termination

Guides: 121, 122, 126, 130, 131, 190



90° Termination


Guides: 124, 133, 134



Plug


Straight termination

Guides: 111




90° Termination

Guides: 110, 125, 191



Surface mount termination

Guides: 110, 125, 191



(1) Important note: See important note on 1HB preparation board details (page 17).

* Theoretical dimensions

Technical Characteristics

Materials & Platings

Insulator	LCP Thermoplastic
Contact	Copper Alloy
Guide	Brass + Ni plating or Stainless Steel
Contact plating	Ni + Au

Environmental

Temperature range	- 55° C to +125° C
Safety of contact from extraction	Statical 2 mm / 0.079" Dynamical 1.80 mm / 0.071"
Mating cycles	5000
Withdrawal forces	≤ 0.5 N
Special contacts	According to NFC 93569

Electrical

Contact resistance	Signal ≤ 12 mΩ
Current rating	Signal 3 A
Insulation	>10 ⁴ MΩ
Voltage rating	200 V
Proof voltage	800 V
Contact diameter	Signal 0.50 mm

How To Order



MDP

1



2



3



4




5

1 Series					
2 Arrangement	2 0 0				
3 Part - Polarity Plating	<table border="0"> <tr> <td>1 9 Male plug - MIL tinned plating</td> <td>2 8 Female receptacle - MIL tinned plating</td> </tr> </table>	1 9 Male plug - MIL tinned plating	2 8 Female receptacle - MIL tinned plating		
1 9 Male plug - MIL tinned plating	2 8 Female receptacle - MIL tinned plating				
4 Termination Styles	<table border="0"> <tr> <td>1 0 90° termination, PCB thickness 1.60</td> <td>4 4 SMT* - Uncentered PCB thickness 3.80</td> </tr> <tr> <td>3 1 Straight termination, PCB thickness 3.20</td> <td>9 6 Straight termination, PCB thickness 4.50</td> </tr> </table>	1 0 90° termination, PCB thickness 1.60	4 4 SMT* - Uncentered PCB thickness 3.80	3 1 Straight termination, PCB thickness 3.20	9 6 Straight termination, PCB thickness 4.50
1 0 90° termination, PCB thickness 1.60	4 4 SMT* - Uncentered PCB thickness 3.80				
3 1 Straight termination, PCB thickness 3.20	9 6 Straight termination, PCB thickness 4.50				
5 Guide Styles	<table border="0"> <tr> <td>1 1 4 Male unpolarised, vertical mount</td> <td>1 2 2 Female polarised, vertical mount</td> </tr> <tr> <td>1 2 5 Male unpolarised, transverse mount</td> <td>1 3 4 Female polarised, transverse mount</td> </tr> </table>	1 1 4 Male unpolarised, vertical mount	1 2 2 Female polarised, vertical mount	1 2 5 Male unpolarised, transverse mount	1 3 4 Female polarised, transverse mount
1 1 4 Male unpolarised, vertical mount	1 2 2 Female polarised, vertical mount				
1 2 5 Male unpolarised, transverse mount	1 3 4 Female polarised, transverse mount				


* Surface Mount Termination
PCB thickness is in mm

Connector Dimensions

200 Contacts Plug



Receptacle



* Theoretical dimensions


Guide and Termination Styles

Receptacle

Through board solder - 90°

Guide: 134


Ref: 10
PCB: 1.44 - 1.76



Through board solder - Straight

Guide: 122

Ref: 96
PCB: 3.42 - 4.18




Plug

Through board solder - Straight

Guide: 114


Ref: 44
PCB: 3.60 - 4.00



Surface mount (uncentered PCB)

Guide: 125

Ref: 81
PCB: 2.88 - 3.52




Note: for other guide styles requested, please contact technical support.

Contact Board Preparation Details

200 Contact Board Preparation Details Receptacle


Straight termination

Guide: 122



90° Termination


Guide: 134



Plug




Straight termination

Guide: 114



Surface mount termination

Guide: 125



G view

* Theoretical dimensions

Disclaimer 2018


All of the information included in this catalogue is believed to be accurate at the time of printing. It is recommended, however, that users should independently evaluate the suitability of each product for their intended application and be sure that each product is properly installed, used and maintained to achieve desired results.

Smiths Interconnect makes no warranties as to the accuracy or completeness of the information, and disclaims any liability regarding its use.

Smiths Interconnect reserves the right to modify design and specifications, in order to improve quality, keep pace with technological development or meet specific production requirements.

No reproduction or use without express permission of editorial and pictorial content, in any manner.

Product Portfolio



- Antenna Systems
- Cable Assemblies
- Connector Solutions
- Ferrite Components & Assemblies
- RF Filter Components & Assemblies
- Integrated Microwave Assemblies
- Millimeter-Wave Solutions
- RF Components
- Test Sockets and WLCSP Probe Heads
- Time & Frequency Systems

Global Support

UK Headquarters

- London, UK
+44 20 7004 1600
info.uk@smithsinterconnect.com

US Headquarters

- Stuart, FL
+1 772 286 9300
info.us@smithsinterconnect.com

Americas

- Costa Mesa, CA
+1 714 371 1100
info.us@smithsinterconnect.com
- Milpitas, CA
+1 408 957 9607 x 1125
info.us@smithsinterconnect.com
- Stuart, FL
+1 772 286 9300
info.us@smithsinterconnect.com
- Hudson, MA
+1 978 568 0451
info.us@smithsinterconnect.com
- Northampton, MA
+1 413 582 9620
info.northampton@smithsinterconnectinc.com
- Tampa, FL
+ 1 813 901 7200
info.tampa@smithsinterconnectinc.com
- Kansas City, KS
+1 913 342 5544
info.us@smithsinterconnect.com
- Salisbury, MD
+1 800 780 2169
info.us@smithsinterconnect.com
- Thousand Oaks, CA
+1 805 267 0100
info.thousandoaks@smithsinterconnectinc.com

Europe

- Deggendorf, Germany
+49 991 250 120
info.de@smithsinterconnect.com
- Genova, Italy
+39 0 10 60361
info.it@smithsinterconnect.com
- Dundee, UK
+44 1382 427 200
info.dundee@smithsinterconnect.com
- Rouen, France
+33 2 32 96 91 76
info.fr@smithsinterconnect.com
- Elstree, UK
+44 20 8236 2400
info.uk@smithsinterconnect.com

Asia

- Shanghai, China
+86 21 3318 4650
info.asia@smithsinterconnect.com
- Suzhou, China
+86 512 6273 1188
info.asia@smithsinterconnect.com
- Singapore
+65 6846 1655
info.asia@smithsinterconnect.com