

TABLE 1

SHELL SIZE	A MAX	B THREAD
09	21,0	0.625-0.1P-0.3L-TS
11	24,5	0.750-0.1P-0.3L-TS
13	28,0	0.875-0.1P-0.3L-TS
15	30,0	1.000-0.1P-0.3L-TS
17	34,0	1.1875-0.1P-0.3L-TS
19	37,0	1.250-0.1P-0.3L-TS
21	40,0	1.375-0.1P-0.3L-TS
23	43,0	1.500-0.1P-0.3L-TS
25	47,0	1.625-0.1P-0.3L-TS

TABLE 2

EYELET REF.	F
01	3,2
02	3,7
03	4,3
04	5,3
05	6,4

TABLE 3

RING REF.	E MAX
09	18,0
11	21,4
13	25,8
15	28,8
17	32,0
19	35,0
21	38,3
23	41,7
25	44,6

TABLE 4

CODE	LANYARD TYPE
WR	NYLON COVERED STAINLESS STEEL WIRE ROPE
TC	TEFLON COVERED STAINLESS STEEL WIRE ROPE
LC	STAINLESS STEEL LINK CHAIN
R	OLIVE DRAB POLYESTER CORD


TABLE 5

CODE	MATERIAL	GASKET MATERIAL
1	ALUMINIUM	SILICONE
2	NICKEL ALUMINIUM BRONZE	SILICONE
4	STAINLESS STEEL	VITON
7	BLACK ACETAL	SILICONE
74	COMPOSITE	SILICONE


TABLE 6

CODE	PLATING
B	CADMIUM OLIVE DRAB OVER ELECTROLESS NICKEL
C	ELECTROLESS NICKEL
U	UNPLATED
ZB	ZINC COBALT OLIVE DRAB OVER ELECTROLESS NICKEL
ZN	ZINC NICKEL
Z	SHOT BLAST (NICKEL ALUMINIUM BRONZE ONLY)
J	PASSIVATE (STAINLESS STEEL ONLY)

NOTE 2 - TABLES 4, 5 & 6 NOT EXHAUSTIVE FOR COMPREHENSIVE LIST AND SPECS SEE WEBSITE



100P160-17-1-C  
NO ATTACHMENT VERSION



100P160-17-1-C-EO  
EYELET ONLY VERSION  
(EYELET SIZE OPTIONS NOT AVAILABLE)

INSERT F FOR FLUOROSILICONE GASKET (SEE TABLE 5 FOR STANDARD MATERIAL)  
SERIES \_\_\_\_\_  
SHELL SIZE (TABLE 1) \_\_\_\_\_  
MATERIAL (TABLE 5) \_\_\_\_\_  
PLATING (TABLE 6) \_\_\_\_\_  
LANYARD TYPE (TABLE 4) \_\_\_\_\_  
LANYARD LENGTH (IN INCHES) \_\_\_\_\_  
ATTACHMENT REF. (SEE NOTE 1) \_\_\_\_\_

100P160-17-1-C-WR4-17

100P160 DATA SHEET  
RECEPTACLE PROTECTION CAP  
TO FIT CONNECTOR:  
MIL-DTL-38999 SERIES III

DRAWING NOT TO SCALE - DIMENSIONS IN MM

THIS DRAWING IS THE COPYRIGHT AND THE PROPERTY OF POLAMCO LTD. IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT WRITTEN CONSENT OF THE COMPANY

ISSUE 4  
DATE 22/10/2009



POLAMCO LTD

WESTON LOCK  
LOWER BRISTOL ROAD  
BATH BA2 1EP