



TABLE 1

SHELL SIZE	A THREAD	ØB MAX	C MAX	T ±0,2
09	M12 x 1.0	18,0	15,0	6,9
11	M15 x 1.0	21,0	18,0	10,5
13	M18 x 1.0	24,5	21,0	13,3
15	M22 x 1.0	27,5	25,4	16,5
17	M25 x 1.0	31,0	28,6	19,7
19	M28 x 1.0	34,0	31,8	22,2
21	M31 x 1.0	37,0	34,0	25,4
23	M34 x 1.0	40,0	37,0	28,6
25	M37 x 1.0	43,5	40,0	31,8

TABLE 2

CODE	MATERIAL / PLATING
1-C	ALUMINIUM / ELECTROLESS NICKEL
1-B	ALUMINIUM / CADMIUM OLIVE DRAB OVER ELECTROLESS NICKEL
1-ZB	ALUMINIUM / ZINC COBALT OLIVE DRAB OVER ELECTROLESS NICKEL
1-ZN	ALUMINIUM / ZINC NICKEL BLACK PASSIVATE OVER ELECTROLESS NICKEL
1-G	ALUMINIUM / BLACK ANODISE, SULPHURIC
4-J	STAINLESS STEEL / PASSIVATE
2-Z	NICKEL ALUMINIUM BRONZE / SHOT BLAST

SEE SS0076 FOR FULL RANGE OF FINISH OPTIONS

76H1-17-1-C
 SERIES _____
 CONNECTOR INTERFACE _____
 ANGLE _____
 SHELL SIZE (TABLE 1) _____
 MATERIAL (TABLE 2) _____
 FINISH (TABLE 2) _____

DRAWN		DATE		 3RD ANGLE PROJECTION NOT TO SCALE	PART NUMBER:			 76H SERIES				
J.CLARK		05/08/2010			TITLE:						LOW PROFILE SPIN COUPLING ADAPTOR TO TAKE A HEAT SHRINK BOOT	
DESIGN APPROVAL		DATE		UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN MILLIMETRES GENERAL TOL LINEAR +/-0,25MM ANGULAR +/- 1°				ASSY USED ON: MIL-DTL-38999 SERIES III & IV				
K.SHEPPARD		17/12/2010			THIS DRAWING IS COPYRIGHT AND THE PROPERTY OF POLAMCO LTD IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT OF THE COMPANY.						POLAMCO LTD, WESTON LOCK, LOWER BRISTOL ROAD BATH BA2 1EP	
DOC TYPE	Customer Drawing							MATERIAL		SEE PART NUMBER BREAKDOWN		
ISSUE/REV	AA		DCR		FINISH		SEE PART NUMBER BREAKDOWN		1		P10076	
NCAGE CODE U5792		WEIGHT N/A										